

## Hyosung's proven, reliable, full-function ATM.

Designed to provide unprecedented reliability, the 7T is unparalleled in the market. This full-function through-the-wall ATM can easily be upgraded from a cash dispenser to deposit automation and supports large volume transactions. The 7T's highest uptime and minimum maintenance has helped make Hyosung the fastest growing ATM company.

## Features

---

### High Availability

The innovative design and the use of Hyosung manufactured core technologies allows for fast, easy replenishment and reduced down time. The 7T is designed to provide reliability that is unequaled in the market, with minimum maintenance and maximum uptime.

### Flexibility

The Series 7 ATMs can also be easily upgraded from a cash dispenser to deposit automation should an institution decide to implement the technology later.

### Capacity

High capacity, cash dispense capability and the ability to support large volume transactions.



## Specifications

### Dimensions

- Height: 1,383mm (54.4")
- Width: 721mm (28.4")
- Depth: 815mm (32.1")
- Weight: 715kg (1,576.3lbs)

### Environmental Conditions

- Temperature: 32°F - 104°F (0°C - 40°C)  
With Heater: 14°F - 104°F (-10°C ~ 40°C)
- Humidity: 25% - 85%

### System Platform

- Microsoft Windows® 10
- Hyosung Moniplus™ XFS

### Customer Interface

- 15" LCD touch screen
- Privacy filter
- PCI complaint EPP
- Headphone jack with Volume Control
- Card Reader – DIP reader, EMV compliant
- Contactless – Integrated reader (via card, smartphone, or smartwatch)

### Media Handling

- Cash Dispenser
  - Configurable denominations up to 4 high capacity dispense cassettes
  - 3,000 notes\* per cassette
  - Bundle present, bundle retract
  - Note by note rejection
  - Automatic shutter
- Cash & Check InModule (CCIM)
  - Maximum capacity Mixed 50 cash/checks per bundle per transaction
  - Up to 2,000 notes\* cassette capacity
  - Up to 2,000 checks\* cassette capacity
  - Reject and retract capability

### Security

- UL291 Level 1 Safe
- Seismic & Heat detector
- Locking Device – Electronic, mechanical combination lock, Kaba Mas Cencon lock (optional)
- IP or Analog security camera (optional)
- Awareness Mirror
- Hyosung MoniGuard™ Solutions
- Trusted Platform Module (TPM)

### Servicing

- Rear access
- State of health indicators for all modules

### Printer

- 3.1" graphical thermal receipt printer

### Power Supply

- AC 100V ~ 127V±10%,  
200V ~ 240V±10% 50/60Hz

### Additional Features

- Backup battery reserves the last transaction & safe shutdown
- Heater support operating
- Barcode reader (optional)

\* Subject to media quality and other variables

Internal Components may change with introduction of new technology. Hyosung TNS reserves the right to change the specifications of this ATM to accommodate the changes in technology.

